

AMENDMENTS TO THE CLAIMS

1. **(Currently amended)** A joint prosthesis, comprising:
 - a head member so sized and shaped as to be articulatable with a joint socket, the head member defining a head bore;
 - a neck member, having
 - a base;
 - a plug protruding from the base so sized and shaped as to be receivable in the head bore; and
 - a spigot protruding from the base, the spigot having a first cylinder adjacent the base, and a second cylinder having a diameter and being disposed adjacent the first cylinder, the first cylinder having a diameter greater than the diameter of the second cylinder; and
 - a stem member, having
 - a proximal end defining a stem bore, the stem bore sized and shaped for receiving the spigot and having a first cylindrical portion for engaging the periphery of the first cylinder of the spigot by friction-tight press-fit with the first cylindrical portion of the stem bore ~~when the stem bore first cylindrical portion receives the first cylinder of the spigot~~; and
 - a shaft extending from the proximal end and being sized and shaped for seating in a cavity of a long bone.

2. (Original) The joint prosthesis of claim 1, wherein the base of the neck member defines at least one receptacle.
3. (Original) The joint prosthesis of claim 2, wherein the stem member further comprises a key protruding from the proximal end, the key so positioned as to be received in the at least one receptacle of the neck member as the stem bore receives the spigot.
4. (Original) The joint prosthesis of claim 3, wherein the base of the neck member further defines a plurality of receptacles, and the key is selectively positionable in one of the plurality of receptacles.
5. (Original) The joint prosthesis of claim 1, wherein the spigot further comprises a transition zone of tapering diameter positioned between the first cylinder and the second cylinder.
6. (Original) The joint prosthesis of claim 1, further comprising a protrusion fixedly located in the stem bore, wherein the spigot is distally so split as to define thereby at least one axially oriented slot, and wherein the protrusion is sized, shaped, and positioned for insertion into the axially oriented slot as the spigot is inserted into the stem bore, the protrusion further being sized and shaped for radially expanding the spigot to secure the spigot within the stem bore as the spigot becomes fully seated in the stem bore.

7. (Original) The joint prosthesis of claim 1, wherein the stem member further comprises a distal end, the distal end defining at least one axially oriented slot.
8. (Original) The joint prosthesis of claim 1, wherein the shaft terminates in a distal end having at least three tines defined by slots in the shaft, the slots forming an acute angle.
9. (Original) The joint prosthesis of claim 1, wherein the base of the neck member has a longitudinal axis, and wherein the spigot and the plug protrude from the base in the same plane, the spigot protruding at substantially a right angle to the longitudinal axis of the base, and the plug protruding at an angle of 40 to 50 degrees relative to the longitudinal axis of the base.

Claims 10-12 (canceled)

13. **(Currently amended)** A joint prosthesis, comprising:
 - a head member so sized and shaped as to be articulatable with a joint socket, the head member defining a head bore;
 - a neck member, having
 - a base;
 - a plug protruding from the base so sized and shaped as to be receivable in the head bore; and

a spigot protruding from the base and including a locking band with a
constant cross-sectional geometry along its length; and
a stem member, having
a proximal end defining a stem bore, the stem bore sized and shaped for
receiving the spigot, the bore having a receiving portion with a
constant cross-sectional geometry ~~that is smaller than that of the~~
~~locking band for, the receiving portion~~ engaging the locking band of
the spigot in the stem bore by friction-tight press-fit ~~as, with~~ the neck
member ~~becomes~~ fully seated on the stem member; and
a shaft extending from the proximal end and being sized and shaped for
seating in a cavity of a long bone.

14. (Previously presented) The joint prosthesis of claim 13, wherein the locking band and the receiving portion are substantially cylindrical.
15. (Original) The joint prosthesis of claim 13, wherein the spigot has a free end that terminates with a taper.
16. (Original) The joint prosthesis of claim 13, wherein the base of the neck member defines at least one receptacle.
17. (Original) The joint prosthesis of claim 16, wherein the stem member further comprises a key protruding from the proximal end, the key so positioned as to be

received in the at least one receptacle of the neck member as the stem bore receives the spigot.

18. (Original) The joint prosthesis of claim 17, wherein the base of the neck member further defines a plurality of receptacles, and the key is selectively positionable in one of the plurality of receptacles.
19. (Currently amended) ~~A stem component of a joint prosthesis, comprising:~~
~~a proximal end; and~~
~~a shaft extending from the proximal end, the shaft sized and shaped for seating in a~~
~~cavity of a long bone, and the shaft terminating~~ The joint prosthesis of
claim 13, wherein the shaft terminates in a distal end having at least three
tines defined by slots in the shaft, the slots forming an acute angle.
20. (Original) The stem component of claim 19, wherein at least one of the tines has at least one sharp cutting edge.
21. (Previously presented) The stem component of claim 19, wherein the distal end has three tines defined by two slots.
22. (Previously presented) The stem component of claim 21, wherein the two slots are oriented longitudinally along the stem and symmetrically, relative to a plane bisecting the stem longitudinally, so that an anterolateral tine is defined by one slot,

a posterolateral tine is defined by the other slot, and a medial tine is defined by both slots.

23. (Previously presented) The stem component of claim 19, wherein each slot is cut completely across the stem cross section.
24. (Previously presented) The stem component of claim 21, wherein the two slots intersect at or adjacent the lateral surface of the stem.
25. (Previously presented) The joint prosthesis of claim 1, wherein the bore defines a second cylindrical portion for engaging the periphery of the second cylinder of the spigot by friction-tight press-fit when the stem bore receives the spigot.